

X-PRIVILO TXS



Wheel Diameter	Item No.	Sizes Description	Sidewall Description	Standard Rim	Section Width (mm)	OA. Diameter (mm)	Max. Pressure (kpa/psi)	UTQG		
								Treadwear	Traction	Temperature
12	TX5R1201	145/70R12 69T	BSW	4.5	150	509	300/44	440	A	A
	TX5R1202	145/80R12 74T	BSW	4.0	145	537	300/44	440	A	A
	TX5R1203	155/70R12 73T	BSW	4.5	157	523	300/44	440	A	A
	TX5R1204	155/80R12 77T	BSW	4.5	157	553	300/44	440	A	A
	TX5R1205	165/70R12 77T	BSW	5.0	170	537	300/44	440	A	A
	TX5R1206	175/70R12 80T	BSW	5.0	177	551	300/44	440	A	A
13	TX5R1301	145/70R13 71T	BSW	4.5	150	534	300/44	440	A	A
	TX5R1302	145/80R13 75T	BSW	4.0	145	562	300/44	440	A	A
	TX5R1303	155/65R13 73T	BSW	4.5	157	532	300/44	440	A	A
	TX5R1304	155/70R13 75T	BSW	4.5	157	548	300/44	440	A	A
	TX5R1305	155/80R13 79T	BSW	4.5	157	578	300/44	440	A	A
	TX5R1306	165/65R13 77T	BSW	5.0	170	544	300/44	440	A	A
	TX5R1307	165/70R13 79T	BSW	5.0	170	562	300/44	440	A	A
	TX5R1308	165/80R13 83T	BSW	4.5	165	594	300/44	440	A	A
	TX5R1309	175/60R13 77H	BSW	5.0	177	540	300/44	440	A	A
	TX5R1310	175/65R13 80T	BSW	5.0	177	558	300/44	440	A	A
	TX5R1311	175/70R13 82T	BSW	5.0	177	576	300/44	440	A	A
	TX5R1312	185/70R13 86T	BSW	5.5	189	590	300/44	440	A	A
14	TX5R1401	155/65R14 75T	BSW	4.5	157	558	300/44	440	A	A
	TX5R1402	155/70R14 77T	BSW	4.5	157	574	300/44	440	A	A
	TX5R1403	165/60R14 75H	BSW	5.0	170	554	300/44	440	A	A
	TX5R1404	165/65R14 79T	BSW	5.0	170	570	300/44	440	A	A
	TX5R1405	165/70R14 81T	BSW	5.0	170	588	300/44	440	A	A
	TX5R1406	175/60R14 79H	BSW	5.0	177	566	300/44	440	A	A
	TX5R1407	175/65R14 82H	BSW	5.5	177	584	300/44	440	A	A
	TX5R1419	175/65R14 86TXL	BSW	5.5	177	584	340/50	440	A	A
	TX5R1408	175/70R14 84T	BSW	5.0	177	602	300/44	440	A	A
	TX5R1420	175/70R14 88TXL	BSW	5.0	177	602	340/50	440	A	A
	TX5R1409	185/50R14 77V	BSW	6.0	194	542	300/44	440	A	A
	TX5R1410	185/55R14 80H	BSW	6.0	194	560	300/44	440	A	A
	TX5R1411	185/60R14 82H	BSW	5.5	189	578	300/44	440	A	A
	TX5R1412	185/65R14 86H	BSW	5.5	189	596	300/44	440	A	A
	TX5R1413	185/70R14 88T	BSW	5.5	189	616	300/44	440	A	A
	TX5R1414	195/60R14 86H	BSW	6.0	201	590	300/44	440	A	A
	TX5R1415	195/65R14 89H	BSW	6.0	201	610	300/44	440	A	A
	TX5R1416	195/70R14 91T	BSW	6.0	201	630	300/44	440	A	A
TX5R1417	205/60R14 88H	BSW	6.0	209	602	300/44	440	A	A	
TX5R1418	205/70R14 95T	BSW	6.0	209	644	300/44	440	A	A	
15	TX5R1501	155/60R15 74T	BSW	5.0	157	567	300/44	440	A	A
	TX5R1502	165/60R15 81TXL	BSW	5.0	170	579	340/50	440	A	A
	TX5R1503	165/65R15 81T	BSW	5.0	170	595	300/44	440	A	A
	TX5R1504	175/55R15 77T	BSW	5.5	182	573	300/44	440	A	A
	TX5R1505	175/60R15 81V	BSW	5.0	177	591	300/44	440	A	A
	TX5R1506	175/65R15 84H	BSW	5.0	177	609	300/44	440	A	A
	TX5R1507	185/55R15 82V	BSW	6.0	194	585	300/44	440	A	A
	TX5R1508	185/60R15 84H	BSW	5.5	189	603	300/44	440	A	A
	TX5R1519	185/60R15 88HXL	BSW	5.5	189	603	340/50	440	A	A