

# X-PRIVILO TXS

## COMFORT PCR



Wheel Diameter	Item No.	Sizes Description	Sidewall Description	Standard Rim	Section Width (mm)	OA. Diameter (mm)	Max. Pressure (kpa/psi)	UTQG		
								Treadwear	Traction	Temperature
15	TX5R1509	185/65R15 88H	BSW	5.5	189	621	300/44	440	A	A
	TX5R1520	185/65R15 92HXL	BSW	5.5	189	621	340/50	440	A	A
	TX5R1510	195/50R15 82V	BSW	6.0	201	577	300/44	440	A	A
	TX5R1511	195/55R15 85V	BSW	6.0	201	595	300/44	440	A	A
	TX5R1512	195/60R15 88V	BSW	6.0	201	615	300/44	440	A	A
	TX5R1521	195/60R15 88H	BSW	6.0	201	615	300/44	440	A	A
	TX5R1513	195/65R15 91V	BSW	6.0	201	635	300/44	440	A	A
	TX5R1522	195/65R15 95HXL	BSW	6.0	201	635	340/50	440	A	A
	TX5R1514	205/60R15 91V	BSW	6.0	209	627	300/44	440	A	A
	TX5R1515	205/65R15 94V	BSW	6.0	209	647	300/44	440	A	A
	TX5R1523	205/65R15 94H	BSW	6.0	209	647	300/44	440	A	A
	TX5R1516	205/70R15 96T	BSW	6.0	209	669	300/44	440	A	A
	TX5R1517	215/65R15 96H	BSW	6.5	221	661	300/44	440	A	A
	TX5R1524	215/65R15 100HXL	BSW	6.5	221	661	340/50	440	A	A
TX5R1518	215/70R15 98T	BSW	6.5	221	683	300/44	440	A	A	
16	TX5R1601	175/50R16 77V	BSW	5.5	182	582	300/44	440	A	A
	TX5R1602	185/50R16 81V	BSW	6.0	194	592	300/44	440	A	A
	TX5R1603	185/55R16 83V	BSW	6.0	194	610	300/44	440	A	A
	TX5R1604	195/50R16 84V	BSW	6.0	201	602	300/44	440	A	A
	TX5R1605	195/55R16 87V	BSW	6.0	201	620	300/44	440	A	A
	TX5R1606	195/60R16 89H	BSW	6.0	201	641	300/44	440	A	A
	TX5R1607	205/50ZR16 87W	BSW	6.5	214	612	300/44	440	A	A
	TX5R1608	205/55R16 91V	BSW	6.5	214	632	300/44	440	A	A
	TX5R1609	205/60R16 92V	BSW	6.0	209	652	300/44	440	A	A
	TX5R1610	205/65R16 95H	BSW	6.0	209	672	300/44	440	A	A
	TX5R1611	215/55ZR16 97WXL	BSW	7.0	226	642	340/50	440	A	A
	TX5R1612	215/60R16 95V	BSW	6.5	221	664	300/44	440	A	A
	TX5R1617	215/60R16 99HXL	BSW	6.5	221	664	340/50	440	A	A
	TX5R1613	215/65R16 98H	BSW	6.5	221	686	300/44	440	A	A
	TX5R1618	215/65R16 102HXL	BSW	6.5	221	686	340/50	440	A	A
	TX5R1614	225/50ZR16 96WXL	BSW	7.0	233	632	340/50	440	A	A
	TX5R1615	225/55ZR16 99WXL	BSW	7.0	233	654	340/50	440	A	A
	TX5R1616	225/60R16 98H	BSW	6.5	228	676	300/44	440	A	A