




























ALL TERRAIN

Wheel Diameter	Item No.	Sizes Description	Sidewall Description	Standard Rim	Section Width (mm)	OA. Diameter (mm)	Max. Pressure (kpa/psi)				dB
15	CFA1501	31X10.50R15LT C 109S	RWL	8.5	268	775	350/51	E	C		72
	CFA1502	32X11.50R15LT C 113R	RWL	9.0	292	813	350/51	E	C		72
	CFA1503	33X12.50R15LT C 108R	RWL	10.0	320	838	350/51	E	C		72
	CFA1504	35X12.50R15LT C 113R	RWL	10.0	326	890	350/51	E	C		72
	CFA1505	LT215/75R15 C 100/97R	RWL	6.0	216	703	350/50	E	C		72
	CFA1506	LT235/75R15 C 104/101R	RWL	6.5	235	733	340/50	E	C		72
16	CFA1609	LT215/85R16 E 115/112R	RWL	6.0	216	772	550/80	E	C		72
	CFA1607	LT225/75R16 E 115/112R	RWL	6.0	223	744	550/80	E	C		72
	CFA1610	LT235/85R16 E 120/116R	RWL	6.5	235	806	550/80	E	C		72
	CFA1601	LT245/70R16 D 113/110S	RWL	7.0	248	750	450/65	E	C		72
	CFA1608	LT245/75R16 E 120/116R	RWL	7.0	248	774	550/80	E	C		72
	CFA1602	LT265/70R16 E 121/118S	RWL	8.0	272	778	550/80	E	C		72
	CFA1603	LT265/75R16 E 123/120R	RWL	7.5	267	804	550/80	-	-	-	-
	CFA1604	LT285/75R16 E 126/123R	RWL	8.0	286	834	550/80	-	-	-	-
	CFA1605	LT305/70R16 E 124/121R	RWL	9.0	310	838	550/80	-	-	-	-
CFA1606	LT315/75R16 E 127/124R	RWL	8.5	326	886	550/80	-	-	-	-	
17	CFA1707	33X12.50R17LT D 117R	RWL	10.0	320	838	450/65	E	C		72
	CFA1708	35X12.50R17LT D 121R	RWL	10.0	326	890	450/65	E	C		72
	CFA1701	LT245/65R17 D 110/108S	RWL	7.0	248	750	450/65	E	C		72
	CFA1702	LT245/70R17 E 119/116S	RWL	7.0	248	776	550/80	E	C		72
	CFA1703	LT245/75R17 E 121/118S	RWL	7.0	248	800	550/80	E	C		72
	CFA1704	LT265/65R17 E 120/117S	RWL	7.0	272	776	550/80	E	C		72
	CFA1705	LT265/70R17 E 121/118S	RWL	8.0	272	804	550/80	E	C		72
CFA1706	LT285/70R17 E 126/123R	RWL	8.5	284	831	550/80	-	-	-	-	
18	CFA1805	33X12.50R18LT E 118R	RWL	10.0	320	838	550/80	-	-	-	-
	CFA1806	35X12.50R18LT E 123R	RWL	10.0	320	890	550/80	-	-	-	-
	CFA1801	LT265/60R18 E 119/116S	RWL	8.0	272	775	550/80	-	-	-	-
	CFA1802	LT265/65R18 E 122/119R	RWL	8.0	272	801	550/80	-	-	-	-
	CFA1803	LT275/65R18 E 123/120R	RWL	8.0	279	813	550/80	-	-	-	-
	CFA1804	LT275/70R18 E 125/122R	RWL	8.0	279	843	550/80	-	-	-	-
20	CFA2001	LT265/60R20 E 121/118S	RWL	8.0	272	826	550/80	-	-	-	-
	CFA2002	LT275/65R20 E 126/123S	RWL	8.0	279	866	550/80	-	-	-	-

Wheel Diameter	Item No.	Sizes Description	Sidewall Description	Standard Rim	Section Width (mm)	OA. Diameter (mm)	Max. Pressure (kpa/psi)				dB
16	CFA1611	P265/70R16 112T	RWL	8.0	272	778	300/44	-	-	-	-
	CFA1612	P265/75R16 116T	RWL	7.5	267	804	300/44	-	-	-	-
17	CFA1709	P265/65R17 112T	RWL	7.0	272	776	300/44	-	-	-	-
	CFA1710	P265/70R17 115T	RWL	8.0	272	804	300/44	-	-	-	-
18	CFA1807XL	P265/60R18 114TXL	RWL	8.0	272	775	340/50	-	-	-	-
	CFA1808XL	P265/65R18 116TXL	RWL	8.0	272	801	340/50	-	-	-	-
20	CFA2003XL	P265/50R20 111HXL	RWL	9.0	277	774	340/50	-	-	-	-
	CFA2004XL	P265/55R20 115HXL	RWL	8.5	274	800	340/50	-	-	-	-