





# PRIMETOUR


## UTQG: 420 A B




Four main grooves provide good driving stability and wet performance.



Reasonable pattern area, perfect collocation of every grooves..



Special tread compound, ensure tire performance stability in all kinds of weather conditions.



White sidewall rib shows extraordinary appearance.

Wheel Diameter	Item No.	Sizes Description	Sidewall Description	Standard Rim	Section Width (mm)	OA. Diameter (mm)	Max. Pressure (kpa/psi)				dB
14	PTP1401	P195/75R14 92S	WSW	5.0	196	648	300/44	-	-	-	-
	PTP1402	P205/75R14 95S	WSW	5.5	203	664	300/44	-	-	-	-
15	PTP1501	P205/70R15 95S	WSW	6.0	209	669	300/44	-	-	-	-
	PTP1502	P205/75R15 97T	WSW	5.5	203	689	300/44	-	-	-	-
	PTP1503	P215/75R15 100T	WSW	6.0	216	703	300/44	-	-	-	-
	PTP1504	P225/70R15 100T	WSW	6.5	228	697	300/44	-	-	-	-
	PTP1505	P225/75R15 102T	WSW	6.0	223	719	300/44	-	-	-	-
	PTP1506	P235/75R15 105S	WSW	6.5	235	733	300/44	-	-	-	-