

ON/OFF ROAD ALL POSITION TIRE FOR MIXED SERVICE APPLICATIONS

- Special chip/cut compound for longer tire life and resistance to scrape, chips, and cuts
- Designed for refuse trucks, oil patch vehicles, logging, mining, and concrete mixers
- Four rib unique tread design for improved traction
- Optimized footprint for improved weight distribution
- 4 belt construction for casing durability and retreading



SAP CODE	SIZE	PLY RATING	LOAD RANGE	LOAD SPEED INDEX	TREAD DEPTH (32ND)	MAX LOAD SINGLE (LBS)	MAX PRESSURE SINGLE (PSI)	MAX LOAD DUAL (LBS)	MAX PRESSURE DUAL (PSI)	RIM WIDTH (IN)	OD (IN)	SW (IN)	REVS / MILE	WEIGHT (LBS)	TREAD CONSTRUCTION
2381030210	11R22.5	16PR	H	146/143K	24	6610	120	6005	120	8.25	41.5	11.0	486	121.3	1S+4S
2391030210	11R24.5	16PR	H	149/146K	24	7160	130	6610	130	8.25	43.5	11.0	464	129.5	1S+4S
2571030210	275/70R22.5	18PR	J	148/145K	23	6940	130	6395	130	8.25	37.7	10.9	535	110.6	1S+4S
2641030210	315/80R22.5	20PR	L	161/157K	24	10000	130	8270	130	9.00	42.4	12.3	476	145.7	1S+4S

ALL POSITION

MIXED SERVICE