

PREMIUM 5 RIB ALL POSITION TIRE

- Solid shoulder design prevents irregular wear and improved mileage
- 5 rib, 4 groove design maximizes water evacuation
- Stone ejectors to protect the casing for retreading
- Optimized bead bundle to reduce wear, reduce chafing, and improve durability
- 4 belt construction for casing durability and retreading
- SmartWay® verified



ALL POSITION

REGIONAL

SAP CODE	SIZE	PLY RATING	LOAD RANGE	LOAD SPEED INDEX	TREAD DEPTH (32ND)	MAX LOAD SINGLE (LBS)	MAX PRESSURE SINGLE (PSI)	MAX LOAD DUAL (LBS)	MAX PRESSURE DUAL (PSI)	RIM WIDTH (IN)	OD (IN)	SW (IN)	REVS / MILE	WEIGHT (LBS)	TREAD CONSTRUCTION
2370038602	10R22.5	14PR	G	141/139L	18	5675	115	5355	115	7.50	40.1	10.3	503	99.8	1S+4S
2380038602*	11R22.5	14PR	G	144/142L	18	6175	105	5840	105	8.25	41.5	11.0	486	111.4	1S+4S
2381038602*	11R22.5	16PR	H	146/143L	18	6610	120	6005	120	8.25	41.5	11.0	486	111.4	1S+4S
2390038602*	11R24.5	14PR	G	146/143L	18	6610	105	6005	105	8.25	43.5	11.0	464	119.5	1S+4S
2391038602*	11R24.5	16PR	H	149/146L	18	7160	120	6610	120	8.25	43.5	11.0	464	119.5	1S+4S
2610030602*	295/75R22.5	14PR	G	144/141L	18	6175	110	5675	110	9.00	39.9	11.7	505	106.9	1S+4S
2611030602*	295/75R22.5	16PR	H	146/143L	18	6610	120	6005	120	9.00	39.9	11.7	505	106.9	1S+4S
2590030602*	285/75R24.5	14PR	G	144/141L	18	6175	110	5675	110	8.25	41.3	11.2	505	112.1	1S+4S
2591030602*	285/75R24.5	16PR	H	147/144L	18	6780	120	6175	120	8.25	41.3	11.2	505	112.1	1S+4S
2502030602	215/75R17.5	16PR	H	135/133L	15	4805	125	4540	125	6.00	30.2	8.3	668	58.1	1S+4S
2510030602	225/70R19.5	12PR	F	125/123L	15	3640	95	3415	95	6.75	32.0	8.9	632	65.2	1S+3S
2511030602	225/70R19.5	14PR	G	128/126L	15	3970	110	3750	110	6.75	32.0	8.9	632	65.2	1S+3S
2521030602	235/75R17.5	18PR	J	143/141J	15	6005	125	5675	125	6.75	31.4	9.2	643	66.0	1S+4S
2535031602	245/70R17.5	18PR	J	136/134M	17	4940	125	4675	125	7.50	30.9	10.0	652	68.7	1S+4S
2535030602	245/70R17.5	18PR	J	143/141J	17	6005	125	5675	125	7.50	30.9	10.0	652	68.7	1S+4S
2540031602	245/70R19.5	14PR	G	133/131M	16	4540	110	4300	110	7.50	33.1	10.0	611	73.4	1S+4S
2541030602	245/70R19.5	16PR	H	136/134M	16	4940	120	4675	120	7.50	33.1	10.0	611	73.4	1S+4S
2560038602	265/70R19.5	14PR	G	137/134M	18	5070	110	4675	110	7.50	34.5	10.3	591	82.2	1S+4S
2550030602	255/70R22.5	16PR	H	140/137M	17	5510	120	5070	120	7.50	36.6	11.0	551	84.7	1S+4S
2571030602	275/70R22.5	18PR	J	148/145L	18	6940	130	6390	130	8.25	37.7	10.9	535	107.1	1S+4S

*SmartWay® verified