

CLOSED SHOULDER DRIVE TIRE

- Optimized block design for enhanced traction and longer mileage
- Closed shoulder design promotes even shoulder wear and longer mileage
- Optimized sipes enhance starting and braking
- 4 belt construction for casing durability and retreading
- 30/32nds tread depth
- SmartWay® verified



SAP CODE	SIZE	PLY RATING	LOAD RANGE	LOAD SPEED INDEX	TREAD DEPTH (32ND)	MAX LOAD SINGLE (LBS)	MAX PRESSURE SINGLE (PSI)	MAX LOAD DUAL (LBS)	MAX PRESSURE DUAL (PSI)	RIM WIDTH (IN)	OD (IN)	SW (IN)	REVS / MILE	WEIGHT (LBS)	TREAD CONSTRUCTION
2380031106	11R22.5	14PR	G	144/142L	30	6175	105	5840	105	8.25	41.5	11.0	486	133.8	1S+4S
2381031106	11R22.5	16PR	H	146/143L	30	6610	120	6005	120	8.25	41.5	11.0	486	133.8	1S+4S
2390031106	11R24.5	14PR	G	146/143L	30	6610	105	6005	150	8.25	43.5	11.0	464	141.9	1S+4S
2391031106	11R24.5	16PR	H	149/146L	30	7160	120	6610	120	8.25	43.5	11.0	464	141.9	1S+4S
2590031106	285/75R24.5	14PR	G	144/141L	30	6175	110	5675	110	8.25	41.6	11.2	505	133.3	1S+4S
2591031106	285/75R24.5	16PR	H	147/144L	30	6780	120	6175	120	8.25	41.6	11.2	505	133.3	1S+4S
2610031106	295/75R22.5	14PR	G	144/141L	30	6175	110	5675	110	9.00	40.2	11.7	505	128.4	1S+4S
2611031106	295/75R22.5	16PR	H	146/143L	30	6610	120	6175	120	9.00	40.2	11.7	505	128.4	1S+4S

DRIVE

LONG HAUL