

CLOSED SHOULDER SUPER-REGIONAL DRIVE TIRE

- Designed for high-speed performance, longer mileage, and minimized shoulder wear
- Specially designed pattern block shape and optimized footprint improves tire grip and traction
- 27/32nds tread depth
- 4 belt construction for casing durability and retreading
- Unique siping for better heat dispersion and enhanced traction



SAP CODE	SIZE	PLY RATING	LOAD RANGE	LOAD SPEED INDEX	TREAD DEPTH (32ND)	MAX LOAD SINGLE (LBS)	MAX PRESSURE SINGLE (PSI)	MAX LOAD DUAL (LBS)	MAX PRESSURE DUAL (PSI)	RIM WIDTH (IN)	OD (IN)	SW (IN)	REVS / MILE	WEIGHT (LBS)	TREAD CONSTRUCTION
2380030131	11R22.5	14PR	G	144/142L	26	6175	105	5840	105	8.25	41.5	11.0	486	121.7	1S+4S
2381030131	11R22.5	16PR	H	146/143L	26	6610	120	6005	120	8.25	41.5	11.0	486	121.7	1S+4S
2390030131	11R24.5	14PR	G	146/143L	26	6610	105	6005	105	8.25	43.5	11.0	464	129.7	1S+4S
2391030131	11R24.5	16PR	H	149/146L	26	7160	120	6610	120	8.25	43.5	11.0	464	129.7	1S+4S
2610030131	295/75R22.5	14PR	G	144/141L	28	6175	110	5675	110	9.00	40.0	11.7	505	115.7	1S+4S
2611030131	295/75R22.5	16PR	H	146/143L	28	6610	120	6005	120	9.00	40.0	11.7	505	115.7	1S+4S

DRIVE

LONG HAUL