



## OPEN SHOULDER DRIVE TIRE

- Open shoulder design provides extra traction
- Tie-bar linked tread blocks prevent irregular wear
- Unique siping helps maintain block rigidity
- 4 belt construction for casing durability and retreading
- SmartWay® verified



SAP CODE	SIZE	PLY RATING	LOAD RANGE	LOAD SPEED INDEX	TREAD DEPTH (32ND)	MAX LOAD SINGLE (LBS)	MAX PRESSURE SINGLE (PSI)	MAX LOAD DUAL (LBS)	MAX PRESSURE DUAL (PSI)	RIM WIDTH (IN)	OD (IN)	SW (IN)	REVS / MILE	WEIGHT (LBS)	TREAD CONSTRUCTION
2511030601	225/70R19.5	14PR	G	128/126L	19	3970	110	3750	110	6.75	32.0	8.9	632	65.4	1S+3S
2540030601	245/70R19.5	14PR	G	133/131L	19	4540	110	4300	110	7.50	33.1	9.8	611	72.8	1S+4S
2380031601*	11R22.5	14PR	G	144/142L	26	6175	105	5840	105	8.25	41.5	11.0	486	119.1	1S+4S
2381031601*	11R22.5	16PR	H	146/143L	26	6610	120	6005	120	8.25	41.5	11.0	486	119.1	1S+4S
2390031601*	11R24.5	14PR	G	146/143L	26	6610	105	6005	105	8.25	43.5	11.0	464	127.1	1S+4S
2391031601*	11R24.5	16PR	H	149/146L	26	7160	120	6610	120	8.25	43.5	11.0	464	127.1	1S+4S
2590031601*	285/75R24.5	14PR	G	144/141L	26	6175	110	5675	110	8.25	41.6	11.2	505	119.5	1S+4S
2591031601*	285/75R24.5	16PR	H	144/141L	26	6780	120	6175	120	8.25	41.6	11.2	505	119.5	1S+4S
2610031601	295/75R22.5	14PR	G	144/141L	26	6175	110	5675	110	9.00	40.2	11.7	505	115.4	1S+4S
2611031601	295/75R22.5	16PR	H	146/143L	26	6610	120	6005	120	9.00	40.2	11.7	505	115.4	1S+4S

\*SmartWay® verified

DRIVE

REGIONAL