



TRAILER TIRE

- Four groove design for stability and better water evacuation
- Groove protectors to prevent stone drilling and retention
- Unique shoulder design to promote even wear and longer mileage
- Optimized footprint for low rolling resistance and even wear
- 4 belt construction for casing durability and retreading
- 12/32nds tread depth
- SmartWay® verified



| SAP CODE | SIZE | PLY RATING | LOAD RANGE | LOAD SPEED INDEX | TREAD DEPTH (32ND) | MAX LOAD SINGLE (LBS) | MAX PRESSURE SINGLE (PSI) | MAX LOAD DUAL (LBS) | MAX PRESSURE DUAL (PSI) | RIM WIDTH (IN) | OD (IN) | SW (IN) | REVS / MILE | WEIGHT (LBS) | TREAD CONSTRUCTION |
|------------|-------------|------------|------------|------------------|--------------------|-----------------------|---------------------------|---------------------|-------------------------|----------------|---------|---------|-------------|--------------|--------------------|
| 2380038107 | 11R22.5 | 14PR | G | 144/142L | 12 | 6175 | 105 | 5840 | 105 | 8.25 | 41.5 | 11.0 | 486 | 105.4 | 1S+4S |
| 2390038107 | 11R24.5 | 14PR | G | 146/143L | 12 | 6610 | 105 | 6005 | 105 | 8.25 | 43.5 | 11.0 | 464 | 112.8 | 1S+4S |
| 2590038107 | 285/75R24.5 | 14PR | G | 144/141L | 12 | 6175 | 110 | 5675 | 110 | 8.25 | 41.3 | 11.2 | 505 | 105.7 | 1S+4S |
| 2610038107 | 295/75R22.5 | 14PR | G | 144/141L | 12 | 6175 | 110 | 5675 | 110 | 9.00 | 39.9 | 11.7 | 505 | 101.2 | 1S+4S |

TRAILER

LONG HAUL